

Nortown Amateur Radio Club Minutes of the April 18th, 2008 Meeting

Present:

John VA3AAD	Frans VE3VNC	John VA3MDJ
Elliot VA3EJF	David VE3VNE	Bert VE3ENA
Doug VE3EES	Vipi VE3PID	Ian VE3IJS
Martin VE3MHC	Jim VE3GRT	Cyril VA3CJE
Jana VE3BFU		

Recent member-attendees who were absent:

Claus VE3PMD	Bill VE3WHW	Geoff VA3GEG
Chris VE3CNK	Jeff VE3QBZ	Sam VA3SEP
Rej VA3REJ	Tom VE3TEG	Bernie VE3OTR
Jal VE3SOC	Tony VE3VME	Andrew VA3CRA
Paul VE3PGF	Ron VA3CCR	

Guest

John, VA3AAD, welcomed Jana, VE3BFU, who has participated recently in the Club Sunday morning nets, and who operates mobile, using a TS-130S.

Old Business

Repeater – Club Incorporation

John, VA3AAD reported that he had obtained an official Ontario “NUANS” registry report reserving the corporate name “Nortown Amateur Radio Club”.

Those present voted unanimously to incorporate under the Ontario Corporations Act as a “Corporation Without Share Capital”. John, VA3AAD stated that proxies had also been received, in favour of incorporation, from VE3PMD, VE3WHW, VA3GEG, VA3REJ and VE3TEG. (A subsequent proxy in favour has also been received from VE3PGF.)

Accordingly, all five Nortown officers (VA3AAD, VE3VNC, VA3MDJ, VE3GRT and VE3MHC) signed an application form for incorporation. These five members will be the initial “directors” of the Club. A “Certified Copy of a Resolution” was signed by VE3VNC, as Vice-President and by VA3MDJ, as Recording Secretary, authorizing VA3AAD, as Club President, to initiate the filing for incorporation.

VA3AAD stated that Ministry approval normally takes from six to eight weeks.

Club Elections

As called for in the Club constitution, John, VA3AAD, stated that elections for the Executive will be held during the first Club meeting in May (on May 2nd). Since no nominations have been received since the last meeting, a proposed slate of officers has been nominated, as follows:

President	John. VA3MDJ
Vice President	Bert VE3ENA
Recording Secretary	Frans VE3VNC
Corresponding Secretary	Martin VE3MHC
Treasurer	John VA3AAD

John thanked the above members for accepting these nominations.

Further nominations can still be received up until the vote is called at the next meeting. Any member in good standing may submit nominations, in writing, to Martin, VE3MHC, for any Club office, providing that the nominees have been contacted and have agreed to stand.

John, VA3AAD, stated that the Club's fiscal year ends on July 31st, and that before that date each year, the Club usually will have elected a new set of directors, who will form a new executive. This timing is fortuitous, because under the Corporations Act, an Initial Report is due within 60 days of incorporation (now expected sometime in June). This report, and annual reports due thereafter, should then be able, each year, to list the newly elected directors in the one report.

List of Club Assets

Martin. VE3MHC has updated this list but is waiting for further information from Elliott, VA3EJF. This item will be carried over.

Esso Building Antenna

Elliott, VA3EJF, reported that he has made two calls about this antenna, without success, but will continue to try determine whether it could be made available to the Club. He will also attempt to determine whether the building could be made available as a location for a repeater antenna.

VE3DO, Ivan Payne

John, VA3AAD reported that Tony, VE3VME, had received an email from Ivan confirming that he would be able to talk to us at the June 6th meeting, subject to any unanticipated out-of-town commitment. John, VA3AAD will prepare a presentation to hold in readiness, should Ivan not be able to attend.

Club Governance

Martin. VE3MHC initiated a discussion relating to the recent difficulty he had had in getting volunteers to serve on the Club executive. He felt that the job of the President is much too onerous, and that duties should be split more widely among Club members. There was a general consensus that tasks are already well spelled out in the Club by-laws, and that it is up to the President to delegate effectively. John, VA3MDJ, agreed with both points of view, and stated that if elected, he would make sure that various tasks were shared more equitably among the Executive and Club members..

Future Presentations

It was confirmed that the May 2nd presentation would be done by Ian, VE3IJS, and the May 16th one by Martin, VE3MHC. The June 6th talk will be given by Ivan Payne and the June 20th meeting will cover preparations for Field Day (the June 28th weekend), organized by Tony, VE3VME.

New Business

International Amateur Radio Day

Doug, VE3EES, chided the membership for not knowing that this day is being recognized this year on April 18th.

Field Trip to the Military Communications and Electronics Museum in Kingston

Frans, VE3VNC, determined that there was considerable interest in a visit to this museum, this summer, on a Saturday in July. Jim, VE3GRT will enquire about a bus rental. The web site is at:

http://www.c-and-e-museum.org/eng_foyer.html

Repeater Backup

John, VA3MDJ, reported that he had examined the repeater that had been given to the Club by GE Real Estate. It consists of two Motorola GR300 radios with Model 620 Wireless Data Encoders. The radios will output 37W but will need to have their duplexers tuned to the Club's frequency pair. It was agreed that he will arrange to have this work done by someone who has the specialized equipment.

Phoenix IRLP Radio

Elliott, VA3EJF, stated that a radio, similar to the one that we have "lost" is currently on offer on eBay for \$50. It was agreed that he should try to purchase it.

Meeting Raffles

Jim, VE3GRT, stated that his inventory of surplus equipment, donated to the Club in earlier years, has all been disposed of, either through meeting raffles or at hamfests. This has been a significant source of revenue for the Club. He urged members to scour their basements for anything that might be of value, that is radio-related, and that could possibly be of value to another member. These items should be brought to Club meetings, or given to any Club member to bring to a meeting.

There was no consensus as to whether non-radio-related items should be raffled at Club meetings. Jim will try out a few such items, in order to determine whether there is sufficient interest.

Presentation

Bert, VE3ENA, gave a remarkable demonstration of a circuit (see the attached CQ article) that can be used, with an oscilloscope, to show whether diodes, transistors, resistors, capacitors and inductances are faulty. He also demonstrated the use of an audio

signal generator for signal tracing. Finally he showed a transmatch tuner that he had built that demonstrated an extraordinarily high level of workmanship and planning.

Financial

The meeting's coffee collection was \$11.50. There was no equipment raffle.

Next Meeting

Will be held at the same location, at 8:00 PM on Friday, May 2nd. Ian, VE3IJS, is feverously working on the presentation, the subject matter for which is currently classified. Don't miss it. .

73's,

John, VA3AAD

www.eternalchaos.com

Do you ever go through your junk box, dig out parts for a project, and then hesitate when you don't know if they're good or bad? Most of us toss the parts back into the box and either forget about the project or buy new parts. N2OZ has an easy way of checking some of those mystery parts while clearing out your junk box.

Build A Quick and Easy Curve Tracer To Test Components

BY LEW OZIMEK*, N2OZ

My ham shack is probably similar to most shacks which exist in this world. It consists of a predominance of commercial equipment, a smattering of homebrew units, some miscellaneous component parts of every description, and a very limited selection of test equipment.

In recent years commercial gear rapidly has replaced homemade equipment in many amateur stations. The reason for this trend is quite obvious: Available items keep getting better and better and the prices keep getting lower and lower. What other result can be expected? The dearth of homemade amateur items is frustrating. It is the antithesis of my early days in the hobby when the average individual who wanted a piece of electronic gear had little choice but to build it. How much satisfaction, pleasure, and personal technical growth has been lost by the movement towards purchased items? I defy anyone to quantify it.

An important prerequisite to success with homemade gear, however, is the availability of useful test equipment. Before I retired, I was able to borrow electronic test equipment from my place of employment without any difficulty. Now that source is no longer available, and I am reduced to making do with the meager assortment of test equipment I own or borrowing from friends in the hobby.

These facts certainly were prominent in my mind when I read a short article entitled an "Inexpensive Curve Tracer" in my amateur radio club newsletter. The author, M. Chisena, KA2ZEV, presented a schematic with a summary of the performance capability of a simple, versatile tester. The device apparently is well known to skilled technicians in the electronics industry who have used it for many, many years, but its history is lost to antiquity. Its potential capability fascinated me, and I felt that if it could come close to the performance parameters claimed, it would go a long way towards filling a big void in my home shop test capability.

The schematic for this tester is shown in fig. 1. The only components required are a 6.3 VAC transformer, three 150 ohm resistors (1/2 watt or larger), and some test leads. It requires an




Fig. 1— Schematic of the "Curve Tracer" Component Tester. Input transformer is a small 6.3 volt filament unit. All resistors are 1/2 watt or larger.

oscilloscope to provide the display. The only restriction is that the scope must accept separate inputs to the horizontal and vertical circuits. Otherwise anything goes. The scope I used is an old 5 MHz unit that a friend of mine built many years ago as part of a Bell & Howell Schools training course. He left it with me when he moved away, and I was on the verge of throwing it away because it barely provided a meaningful presentation. About all I could see

on it were frequency waves present in a circuit under test without being able to analyze their content. Better scopes are surely available in every fleamarket at miniscule prices. However, my poor excuse for a scope worked superbly with the adapter in fig. 1.

Fig. 2 shows how the unit is connected to the scope. Note that the junction of R1 and R2 is connected to the horizontal input of the scope as well as to the red test lead. The junction of




Fig. 2— Interconnection diagram showing the Curve Tracer connected to an oscilloscope. Only three connections are required on the scope: horizontal input, vertical input, and ground.

*37 Dolphin Lane, Northport, NY 11768




Fig. 3—Pattern displayed on the scope when a diode is tested. (A) Results when black probe is on the cathode and red is on the diode. (B) Results when test leads are reversed. Any reduction in the right angle shows a leaky junction (defective unit).

R2 and R3 goes to the vertical input. The output end of R3 is connected to the black probe and to ground on the oscilloscope. It is a very simple device to be sure.

Construction

Layout and assembly is a snap with so few components involved. Almost all of the parts came from my "junk" box, including a metal case measuring 4" x 2" x 2 1/2". (The enclosure size is primarily controlled by the size of the 6.3 VAC transformer available.) Make all connections to terminal strips fastened appropriately in the case. Run all leads leaving the box through grommets in the sides of the metal




Fig. 4—Test pattern of a zener diode with the black lead on the cathode and the red lead on the anode.




Fig. 5—Thyristor (SCR) test pattern. Again the black probe goes to the cathode and the red to the anode.

enclosure to prevent chafing or wear of the wires. Remember that 110 VAC is being fed to the primary of the transformer. Secure the input power lead inside the case and take suitable precaution when working in this area.

Adjustment

1. Turn off the internal horizontal sweep of the scope by turning the input selector switch to external or off.
 2. Apply power to the tester to generate a horizontal scope sweep synched to the 60 Hz input frequency. Adjust the horizontal length on the scope to just fill the screen.
 3. Short the red and black test leads to produce a vertical line. Adjust it to just fill the vertical screen.
- That is the complete adjustment procedure. Nothing could be simpler!

Operation

The application of alternating voltages to both the horizontal and vertical deflection plates of an oscilloscope creates patterns called *Lissajous* figures. A common application of this tech-

nique is to compare two different frequencies (one frequency applied to the horizontal, the other to the vertical) to calibrate audio-frequency signal generators. In our tester the same frequency is applied to both plates so the *Lissajous* patterns are synchronized and stationary.

In order to use the tester, just touch the black and red probes to the leads of a component under test and observe the pattern on the scope. Since only 6 volts is being applied, there is no danger of damaging a component. In fact, the test leads can be interchanged during test without a problem. The only effect will be an inverse image on the screen for most of the components (not all). This will be shown in the examples below.

There is no limit to the types of discrete components you can test, including diodes, transistors, capacitors, resistors, ICs, and inductors. To effectively use the tester, you should create a catalog of test patterns for the types of components you expect to evaluate. Root through the supply of odds and ends of parts you may have accumulated over the years. Test them and record the results in the manner shown in this article. You will quickly develop the capability of easily evaluating results and recognizing failures. In fact, you may be amazed at how many defective components are stored in your spare-parts coffer. I certainly was. Be aware, though, that these tests provide a "go" "no-go" result. No real quantitative test results ensue.

Test Results

The following are the results of tests performed on miscellaneous components I found in a ruck. The orientation of the test leads is shown for each of the tests with some examples of inverse patterns created when the leads are reversed. Since the black lead is connected to ground, it normally is connected to ground or equivalent of a component if appropriate. The results I obtained are analyzed and discussed as necessary. Any deviation from these normal patterns—such as leaky junctions (less than a 90 degree angle), shorts (vertical line), or opens (horizontal line)—are sure signs of a failure.

Diodes. Place the black probe on the cathode and the red on the anode. The resulting pattern is shown in fig. 3(A). Reversing the leads produces an inverse image as shown in fig. 3(B). The sharp 90 degree angle of the L pattern indicates that the diode is conducting in only one direction of the input AC sine wave.




Fig. 6—Series of test patterns of transistors. (A) is an NPN and (C) is a PNP with the black test lead to the base and the red lead either to the collector or emitter. (B) and (D) are the reverse pattern, resulting when leads are reversed. In (E) a field effect transistor (FET) is shown with the black lead on the anode and red on the drain (D) or on the source (S).

POWERPORT™

35 WATTS
HAND HELD!

Make your HT into a 35 watt base-station, mobil or outdoor event Station. Easily hand-portable, **PowerPort's RF35** is a combined rechargeable power supply and 35 watt RF amplifier in a sturdy carrying case with removable accessory pouches also containing all cables, antennae, & automatic charger for immediate use.

SPECIFICATIONS:
2 meter FM: 2.5 to 5 watts in = 35 watts out.
HT Input: male BNC with 4' of mini coax.
Antennae: super-compact roll-up J pole with 10' of mini coax on a PL 259.
Power supply: 12 V, 9 AH, gel cell, rechargeable with supplied automatic charger.
Dimensions & weight: 7.5" H X 9.5" W X 5" D., 9# approx.

CUTTING EDGE ENTERPRISES
 1803 MISSION #546 SANTA CRUZ CA 95060
ORDERS 800: 206-0115

\$140	\$120	\$77	\$165
\$160	\$180	\$180	\$180

CIRCLE 41 ON READER SERVICE CARD




Fig. 7— (A) is the pattern for different values of resistors. In (B) the pattern of a photo cell is shown with the cell covered and cell exposed to light. Note the change in resistance following the pattern of (A).




Fig. 8— Potentiometer pattern displayed on the scope. The slope depends on the resistance value. A jittery trace when the shaft is rotated indicates a noisy potentiometer.

Any reduction of that sharp angle shows a leaky diode; a good junction will always have a 90 degree (or close to it) angle.

Zener Diode. Again apply the black lead to the cathode and the red to the anode of a low-voltage zener (I used a 3.5 V). The resulting pattern of this diode duplicates fig. 3 with the addition of a turn up at the left edge of the pattern (fig. 4). The extra bend is caused by zener conduction. A zener above 6 volts will not show the turn up because only 6 volts is used in this circuit and no zener conduction occurs until its applied voltage exceeds the zener rating. The inverse is not shown here, but you can try it in your own tests.

SCR Thyristor. The test result of this device is shown in fig. 5. To get a meaningful reading place the black probe on the cathode (C) and the red probe on the anode (A) and short the gate to the anode. (A similar test can be done on TRIACS by using Main Terminals 1 and 2 (MT1, MT2) and bridging over the test probe.)

Transistors. Connect the black lead to the base of a transistor and the red lead to either the collector or emitter. The results are shown in fig. 6(A) for a NPN transistor and fig. 6(C) for a PNP. Reversing the leads results in the inverse pattern shown in figs. 6(B) and 6(D). Note how simple it is to identify NPN and PNP transistors by the patterns produced. A sharp 90 degree angle is important (I can't emphasize this too much.) to ensure that no leakage exists in the junctions. In fig. 6(E) a FET (field effect transistor) is shown. With the black lead on the anode the L pattern will be seen when the red lead is placed on D (drain) or on S (source).

Resistors. No lead orientation is required. The patterns in fig. 7(A) show that a 47K ohm resistor (or higher) presents a horizontal line. This line rotates towards the vertical as the resistance value decreases. It actually is a rough limited quantitative measurement of resistance.

A cadmium sulfide photo cell is shown in fig. 7(B). With the cell covered, the pattern shown is horizontal (open or very high resistance). When it is exposed to light, the trace reverts to a slanted line (resistor).

Potentiometers. Fig. 8 shows the change in a pattern as the control shaft is rotated. This pattern can fall anywhere from horizontal to vertical, depending on the value of resistance. The line jiggles as the shaft is rotated, the potentiometer is noisy.

Capacitors. Fig. 9 presents the change in pattern from a 2000 μ F (vertical line) to a 0.1 μ F (horizontal line) capacitor. No test lead orientation applies. The low limit of my tester ap-


AEA

GRAPHICAL ANTENNA HANDHELD ANALYZERS

The complete line of AEA analyzers are now available **FACTORY DIRECT** at the lowest possible cost. Each analyzer gives a **graphical** display of SWR curves with variable sweep width and center frequency. For antenna tuning, you can set the analyzer for a single frequency and a beeping tone will allow you to tune for lowest SWR without having to look at the instrument. The **SWR-121 HF** analyzer covers 1-30 MHz and is priced at **\$299.95**. The **SWR-121 V/U** covers 120-175, 200-225, and 400-475 MHz and is priced at **\$399.95**. Shipping and handling for each unit is \$7.50

The **AEA CableMate™** graphical Time Domain Reflectometer (TDR) is packaged in the same style package as the SWR analyzers. The CableMate shows multiple faults in a cable on the graphical display. Virtually any multi-conductor cable may be tested for shorts, opens or impedance lumps. The CableMate is an excellent device for measuring the length of most any cable. It will also directly show the 25 MHz return loss. The CableMate is priced at \$299.95 plus \$7.50 shipping and handling for a limited time only.

All AEA analyzer products come standard with a serial computer interface. Optional applications software with interface cable is \$29.95 each. With this software you can store the graphical data for your antennas or cables for future reference.



To order any of these products or for further information contact:

AEA
Division of TEMPO RESEARCH CORPORATION
1221 Liberty Way, Vista, CA 92083
Phone: 760-598-9677, Fax: 760-598-4898

Prices and specifications subject to change without notice or obligation




Fig. 9— Patterns of capacitors showing the variation displayed from a 2000 μF down to a 0.1 μF .




Fig. 10— Inductor's test results show a small inductance (1 μH) as a vertical line and a large inductor as a slanted loop.




Fig. 11— Test results of a switch. When the switch is open (infinite resistance), a horizontal line is seen. When it is closed (zero resistance), a vertical line is shown.




Fig. 12— Transistor test results with the black lead to IC ground connection (or V_{SS}) and red lead to all other pins. All pins show the right-angle pattern (like a diode) except for V_{CC} , which includes an additional tail. Any decrease in the right-angle pattern shows a leaky junction.

pears to be 0.1 μF . In order to test smaller capacitors, the frequency of the input voltage must be increased, which may be a worthwhile experiment in the future.

Inductors. My availability of coils was very limited, but two different results are shown in fig. 10.

Switch. The tester shows a short as a vertical line and an open as a horizontal line. Fig. 11 shows the patterns for the two stages of a toggle switch. (Obviously, this test can be used on fuses, continuity checks, etc.)

Integrated Circuits. My miscellaneous ICs are predominantly TTL, so that is what I tested. The black lead is normally connected to ground (or V_{SS}), and the red lead to the other pins in sequence. It helps to have available a diagram of the IC which shows the pin configuration, functions, and internal design. Examples of the importance of correlating results to the design of the IC are presented later on in this article.

Fig. 12 shows the results (all identical) of three different ICs. With black on ground (pin 7) a good 90 degree angle is seen on pins 1 to 6 and 8 to 13 (again, a leaky junction will reduce that angle). The V_{CC} input (pin 14) presents a unique pattern which is acceptable. Fig. 13 shows the design configuration of a SN7400 to allow you to correlate patterns to pin functions.

Fig. 14 is the pattern of a SN7413 with its internal design shown in fig. 15. The importance of the internal design is emphasized because it identifies NC pins (no connection) which show up as opens.

Fig. 16 displays the pattern of a SN7476.

Here again we see the sharp Ls of a good IC and the unique pattern of V_{CC} .

I could keep going, but what I have shown is an excellent start of a signature pattern catalog. Whenever a pattern deviates from the standard, it probably means a failed component. I certainly was surprised at the number of defective components I had stored away. A little more time with this tester and all of my bad parts will be purged.

In Circuit Testing

Experiment with any chassis or unit that you can work on and not miss. But first be sure that **NO POWER IS APPLIED TO A CIRCUIT YOU ARE TESTING** with this device. Conduct the same types of tests described in the previous sections, but be aware that a wired circuit may place special loads and impedances on component junctions which are not present with a non-wired isolated device. The patterns in a wired circuit will not necessarily be identical to those shown in our catalog of signature patterns. My own experience has been that some patterns will be the same and other patterns will be unique, requiring further evaluation. On a questionable transistor, unsolder only the C and E leads and lift them to permit accurate testing of the transistor. One end of a diode may be lifted in a similar manner to verify test results. It is also conceivable that an IC may have to be lifted from the circuit to confirm test results.

To verify performance of my unit as an in-circuit tester, I decided to analyze my Heath

Model 10-4550 10 MHz Dual Trace Oscilloscope. This scope has been inoperative for a number of years, and I gave up trying to repair it about five years ago, when after curing a series of problems, I could not find the source of a failure in the sweep circuits.

Heath "trouble locating guides" normally




Fig. 13— Lead configuration/internal design of an SN7400 IC. Correlate the design to the test patterns in fig. 12.

used voltage measurements to try to pinpoint problems. This was aided and abetted by a strong technical support group at Heath which is now no longer available. With this curve tester I decided to go through the horizontal sweep circuits, checking all of the key components. The entire process took less than an hour (one thing that expedited it is that Heath used sockets to hold ICs so no unsoldering of ICs was necessary). During the tests I found one defective transistor and three defective ICs. It was comforting to verify performance of some FETs and Zeners which had always been question marks to me in the past. I hate to think how many times I replaced a suspect part with

a defective part not knowing that the replacement was bad. Now, finally, the culprits have been identified and replacements ordered. By the time this gets to print, I fully expect to have a working scope once again.

Reprise

I was pleasantly surprised by many things related to this tester. The low cost was expected, but the ease with which it was assembled and tested was a delight. The big point, however, is that the component test results far exceeded my expectations. I was able to make positive evaluations of a wide range of devices with a high




Fig. 14- Test pattern of an SN7413 with the black lead on ground and the red on other pins. The pattern is the same as that of an SN7400 except for pins 3 and 11, which have no internal connection (NC) show up as an open.




Fig. 15- Internal design of an SN7413 to show the correlation of the test pattern to the pin functions.

level of confidence. With this tester I do not have to guess about the performance of parts. In a short time I know! Some individuals may not be comfortable with a "go" "no-go" device and would prefer quantitative tests. Personally, if I'm trying to make a repair, identification of a failed component is all I am interested in.

It is hoped that the reader will build this device and find it as effective as I have. It may lead to your trying your hand at repairing amateur radio gear as well as TVs, VCRs, audio systems, and what have you.

One last note: Horizontal output transistors on TVs and video displays do not test well. Many have built-in damper diodes which look like shorts to this tester.

Good luck and good repairs! ■




Fig. 16- Test pattern of an SN7476 again with the black lead on ground and the red on other pins. Pattern is identical to fig. 12. As with all test patterns, the right angle is important because any decrease indicates a leaky junction and a defective IC.

BRAIN POWER

**SG-500
SMART
POWER
CUBE™
Microprocessor
Controlled Linear Amplifier.
1.8 - 30 MHz***



The SG-500 SmartPowerCube produces tremendous power—nearly as much as a 1 kW amplifier. Yet it requires less than one cubic foot of space. Electronic brain power makes this possible. The SG-500 is an intelligent—microprocessor controlled—high powered linear amplifier, designed with high efficiency transistors. Its electronic brain constantly monitors your HF-SSB's activities, power needs and antenna condition, and automatically—in less than 15 milliseconds—selects the right broadband filter. And it's designed to reliably produce, essentially unattended, in the most demanding conditions. For maximum power—intelligent power—at low cost, the SG-500 SmartPowerCube is just the amplifier you need. Call us for details.

Power Output:
SSB: 500 watts PEP
CW: 500 watts 10 Min. (no fan)
500 watts Unlimited with fan
AM: 250 watts Carrier max.
Band Switching: Fully Automatic
Protection: Input overdrive, Over current, Over temperature
*Export model: 1.8 - 30 MHz, U.S.: 1.8 - 24 MHz. Pending FCC approval.

1-800-259-7331

SGC
NO COMPROMISE
COMMUNICATIONS



The SGC Building 13737 S.E. 26th Street, Box 3526 Bellevue, WA 98009 USA (425)746-6310 Fax: (425)746-6384

CIRCLE 91 ON READER SERVICE CARD

Page Left Blank